

**Prüfbericht 21-00028-CX-GBM-06**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837**

**ANLAGE: 9.1**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41  
 Stand: 29.09.2022



Auto Service

Seite: 1 von 3

**Manufacturer : AUDI, SEAT, SKODA, VOLKSWAGEN**

**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 38  
 Hole circle (mm)/number of holes : 100/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1229	R1-1229	Without	57		565	1937	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : AUDI**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad  
 Accessories : Serie  
 Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI A3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8L	e1*95/54*0042*..., e1*98/14*0042*..	66 - 110	185/65R15		1); 2); 33)
			195/65R15		
		66 - 132	205/60R15		
			132		

**Manufacturer : AUDI, SEAT, SKODA, VOLKSWAGEN**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : SEAT**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
 for Type : 1M  
 Accessories : Serie  
 Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
 for Type : 6J  
 Tightening torque for fixing parts : 120 Nm

commercial type: **IBIZA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6J	e9*2001/116*0067*..	44 - 110	185/60R15		*); only to e9*2001/116*0067*20; 77E; 1); 2); 33)
			185/60R15 M+S		
		55 - 77	175/65R15		
6J	e9*2001/116*0067*..	44 - 51	185/60R15		77E; 1); 2); 33)
		66 - 110	185/60R15		
		77	175/65R15		
		103	175/65R15		

**Prüfbericht 21-00028-CX-GBM-06**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837**

**ANLAGE: 9.1**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41  
 Stand: 29.09.2022



Auto Service

Seite: 2 von 3

commercial type: **SEAT TOLEDO/LEON**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1M	e9*97/27*0026*..	55 - 92	195/65R15		1); 2); 33)
1M	e9*98/14*0026*..	50 - 110	195/65R15		1); 2); 33)

**Manufacturer : AUDI, SEAT, SKODA, VOLKSWAGEN**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : SKODA**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 120 Nm

commercial type: **SKODA OCTAVIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1U	e11*2001/116*0066*..	55	195/65R15 91		1); 2); 33)
		74 - 75	195/65R15 91H		
		110	195/65R15-91V		
1U	e11*2007/46*0011*..	55	195/65R15 91		1); 2); 33)
		74 - 75	195/65R15 91H		
		110	195/65R15-91V		
1U	e11*95/54*0066*..	44 - 110	195/65R15		1); 2); 33)

**Manufacturer : AUDI, SEAT, SKODA, VOLKSWAGEN**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : VOLKSWAGEN**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
for Type : 9C; 9C

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
for Type : 1Y; 9C; 1J; 9N

Tightening torque for fixing parts : 110 Nm for Type : 9C  
120 Nm for Type : 1J; 1Y; 9C; 9N

commercial type: **GOLF / BORA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1J	e1*2001/116*0071*..	50 - 66	195/65R15 91		1); 2); 33)
		74 - 85	195/65R15 91H		
		96 - 110	195/65R15-91V		
1J	e1*96/79*0071*..	50 - 110	195/65R15		1); 2); 33)
1J	e1*98/14*0071*..	50 - 110	195/65R15		1); 2); 33)

commercial type: **NEW BEETLE CABRIOLET MJ 2002-2010**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1Y	e1*2001/116*0205*..	55 - 75	195/65R15 91		*); Convertible; 1); 2); 33)
		77 - 85	195/65R15 91H		
		110	195/65R15-91V		

**Prüfbericht 21-00028-CX-GBM-06**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837**

**ANLAGE: 9.1**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41  
 Stand: 29.09.2022



Auto Service

Seite: 3 von 3

commercial type: **NEW BEETLE MJ 1997-2010**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
9C	e1*2001/116*0106*..	55 - 75	195/65R15 91		1); 2); 33)
		77 - 85	195/65R15 91H		
		110	195/65R15-91V		
9C	e1*97/27*0106*..	66 - 85	195/65R15		1); 2); 33)
9C	e1*98/14*0106*..	55 - 110	195/65R15		1); 2); 33)

commercial type: **VW POLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
9N	e1*2001/116*0174*..	40 - 77	185/60R15 84		*) ; Polo-Fun; Polo-Cross; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Restrictions**

77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.